PROTANK® LIQUID CLEANER

SPRAY TANK CLEANER FOR COMMERCIAL OR FARM USE ONLY

ACTIVE INGREDIENTS:

All ingredients are exempt from the requirements of a tolerance in 40 CFR 180 or are permitted in 21 CFR 184.

KEEP OUT OF REACH OF CHILDREN



Causes serious eye damage. Harmful in contact with skin. Harmful if swallowed. May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Wash hands thoroughly after handling. Wear eye and face protection, protective gloves and protective clothing. Avoid breathing mist or spray. Use only outdoors in a well-ventilated area. Do not eat, drink or smoke when using this product. Store in a well-ventilated and locked place. Keep container tightly closed. Store above 55° F. Do not freeze. Store in original container only. Dispose of contents/container in accordance with Federal, state and local regulations. Do not reuse empty container. Triple rinse (or equivalent) during mixing and loading. Recycling decontaminated containers is the best option of container disposal. The Agricultural Container Recycling Council (ACRC) operates the national recycling program. Contact your state and local ACRC recycler or visit the ACRC web page at www.acrecycle.org. Decontaminated containers may also be disposed of in a sanitary landfill.

FIRST AID

IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison control center or doctor for treatment advice.

IF ON SKIN: Wash with plenty of water. Immediately call a poison control center or doctor for treatment advice. Take off immediately all contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison control center or doctor for treatment advice if you feel unwell.

IF SWALLOWED: Immediately call a poison control center or doctor for treatment advice. Rinse mouth.

For Emergency, Spill, Leak, Fire, Exposure, or Accident, Call: CHEMTREC 1-800-424-9300

IN ALL PURPOSE RIGS:
Lessens contamination when changing from one chemical to another.
IN SINGLE PURPOSE RIGS:
Assures accurate dosage by removing chemicals from the previous batch.
USE BEFORE SPRAYING TO:
Remove scale, dirt, etc. -- Protect pump and valves. -- Reduce strainer clogging. -- Minimize nozzle wear.

Distributed by Winfield Solutions, LLC. P.O. Box 64589, St. Paul, MN 55164-0589

WINFIELD

NET CONTENTS ONE QUART 1/0730/4



DIRECTIONS FOR USE

FOR LARGE TANKS — 100-300 GALLONS: Close boom valve and add 50 gallons of water to tank, then turn on agitation and add <u>one pint of PROTANK LIQUID CLEANER</u>. PROTANK LIQUID CLEANER goes quickly into solution, allowing you to circulate the liquid through the valves, hoses, and pump by opening the bypass valve. Use the hand boom to wash down the tank interior and cover. Once the pump and interior have been cleaned, open boom valve and empty tank by spraying out through boom and nozzles. Take care to observe proper disposal of spray solution. Rinse tank by following the same procedure using water only. A three minute rinse using cold water is necessary, however if you are changing over to a different chemical, a second rinse will lessen the chance of contamination.

When cleaning a tank used for herbicides and chemicals that can cause plant response at low levels, pay particular attention to those parts of the equipment that may absorb the chemical such as hoses, connections, and pump and hand boom packing. Use as directed but in addition allow the rinse solution to remain in the sprayer and its parts overnight. PROTANK LIQUID CLEANER, when used according to label directions, will usually adequately clean the exposed surface of these areas, however, when using these types of chemicals, parts of the sprayer that can absorb product may need to be replaced.

FOR SMALLER TANKS – Fill tank half full of water and use 1 ounce or more for each 3 gallons of the tanks volume.

When using PROTANK LIQUID CLEANER to clean tanks left standing or containing built-up residue from extended use, allow the cleaning solution longer time to act.

PROTANK LIQUID CLEANER's cleansing action may remove rust and scale that was sealing a badly corroded tank, however, it will not harm steel, aluminum, brass or poly tanks and parts if directions concerning rinsing are followed.

Notice of Warranty

Seller warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NOR IS ANY REPRESENTATIVE OF SELLER AUTHORIZED TO MAKE ANY SUCH WARRANTY OR MODIFY THESE TERMS. This warranty does not extend to the storage, handling or use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Seller, and Buyer assumes the risk of any such storage, handling or use. Seller shall not be responsible for incidental or consequential damages, if any, resulting from a breach of warranty.

AgriSolutions[™] is a trademark and Protank[®] is a registered trademark of Winfield Solutions, LLC.