SPEEDWAY®

Water Conditioner AMS REPLACEMENT THAT CONDITIONS HARD WATER TO MAXIMIZE GLYPHOSATE PERFORMANCE

PRINCIPAL FUNCTIONING AGENTS	
Citric acid, alkylamine glycol ethers and phosphate ester	
Constituents Ineffective as Spray Adjuvants	43.6%
TOTAL	
Components exempt from tolerance under 40CFR 180	

KEEP OUT OF REACH OF CHILDREN WARNING

READ ENTIRE LABEL BEFORE USING



Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS

Wash affected areas thoroughly with soap and water after handling. Read and follow all applicable precautionary statements on the accompanying tank mix partner label(s). **Personal Protective Equipment (PPE):** Wear eye and face and hand protection.

FIRST AID

CALL A POISON CONTROL CENTER OR DOCTOR IF YOU FEEL UNWELL

If in eyes: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. If eye irritation persists, get medical advice/attention.

If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

In case of medical emergency, call 1-877-424-7452.

STORAGE AND DISPOSAL

Storage: Store in original container. Keep container tightly closed and locked up. Do not allow water or other chemicals to be introduced into contents of container. Do not contaminate water sources with equipment wash water, spray disposal waste or by cleaning of equipment. Keep away from food, feed or other products to prevent contamination.

Disposal: Do not reuse product containers. Triple rinse (or equivalent), then offer for recycling at an ACRC site (go to http://www.acrecycle.org/ for locations) or by reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by local, state, and federal regulations.

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, Call: CHEMTREC 1-800-424-9300

Warning: This product can expose you to chemicals including Acetaldehyde, which is known to the State of California to cause cancer, and Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

Distributed By: Winfield Solutions, LLC P.O. Box 64589 St. Paul, MN 55164-0589

NET CONTENTS: _____ GAL.

1/0405/9

SPEEDWAY® is a water conditioner concentrate that replaces ammonium sulfate in glyphosate applications by neutralizing antagonizing metal cations. SPEEDWAY® is compatible with most ammonium nitrogen sources, including 32-0-0, 10-34-0 and ammonium sulfate. In some cases, additional ammonium nitrogen may be added to the spray tank to meet specific pesticide label requirements. SPEEDWAY® contains a spray activator technology but does not substitute for a surfactant. If the pesticide label requires a surfactant, use a high quality surfactant at the recommended rate. Do not use with sulfonylurea herbicides. Maintain good equipment hygiene by cleaning pumps, lines and tanks after using this product.

DIRECTIONS FOR USE

Read and follow the applicable restrictions, limitations and directions for use on all product labels involved in tank mixing. Users follow the most restrictive directions for use of each product in the tank mixture. The product precedence over directions for uses referred to on this label.

MIXING INSTRUCTIONS

SHAKE WELL OR RECIRCULATE BEFORE USE

(Recirculate bulk if stored below 32°F)

1. Fill sprayer 1/3 to 1/2 full of water

2. Add SPEEDWAY®

3. Add other adjuvants as required

4. Continue to agitate and add water until tank is full

RECOMMENDED RATES

SPEEDWAY® is intended for use with products registered for agricultural, horticultural, turf, ornamental and non-crop uses.

General Use, pH Reduction & Buffering:

Standard: 1-4 quart(s) per 100 gallons of water, as recommended by manufacturer's pesticide label.

Ground/Air Range:

1-4 quart(s) per 100 gallons of water, as recommended by manufacturer's pesticide label.

For severe hard water conditions or to maximize pesticide activity

Ground/Air: 1-4 quart(s) per 100 gallons of water. Rate used is dependent upon the hardness level in the water. Use higher rates of SPEEDWAY® in areas where the water has a high mineral content.

Notice of Warranty

Seller warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NOR IS ANY REPRESENTATIVE OF SELLER AUTHORIZED TO MAKE ANY SUCH WARRANTY OR MODIFY THESE TERMS. This warranty does not extend to the storage, handling or use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Seller, and Buyer assumes the risk of any such storage, handling or use. Seller shall not be responsible for incidental or consequential damages, if any, resulting from a breach of warranty.

Speedway is a registered trademark of Winfield Solutions, LLC.

4/5/19 - changes to label:

- Update speed way PFA to current Adjuvant's Unilimited's AU-240 formulation.
- Update rates to 1-4 quarts per gallon of spray mix as a general rle of thumb for any ground or aerial equipment recommended by manufacturer's pesticide label; also for general water conditioning.
- Moved Storage and Disposal to front of label
- Removed GHS Study Categories (not required on the label)
- Added PPE Equipment statement under Precautionary Statements
- Rate for water conditioning would depend on hardness level in the water.RER
- Added Prop 65 Warning.