# SAFETY DATA SHEET



Tough 5 EC Herbicide

## **Section 1. Identification**

**GHS** product identifier

.

: Tough 5 EC Herbicide

Other means of identification

: Not available.

**Product code** 

: EPA Registration Number: 91746-5

**Product use** 

: Pesticide

Supplier's details

: Belchim Crop Protection

2751 Centerville Road, Suite 100

Wilmington, DE 19808 1-855-445-7990

e-mail address of person responsible for this SDS

: regulatory@belchim.com

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24 hours per day / 7 days a week)

## Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

**GHS label elements** 

Hazard pictograms





Signal word

: Warning

**Hazard statements** 

: Flammable liquid and vapor. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

**Precautionary statements** 

**Prevention** 

: Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Avoid breathing dust or mist. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response

: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Storage** 

: Store in a well-ventilated place. Keep cool.

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 1/15

# Section 2. Hazards identification

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

identification

Other means of

: Mixture

: Not available.

Product code : EPA Registration Number: 91746-5

Ingredient name	%	CAS number
pyridate (ISO)	≥50 - ≤75	55512-33-9
cyclohexanone	≥10 - ≤25	108-94-1
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	≤10	-
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	≤5	9038-95-3
calcium dodecylbenzenesulphonate	≤3	26264-06-2
2-ethylhexan-1-ol	≤3	104-76-7
octane-1-thiol	≤0.3	111-88-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 2/15

## Section 4. First aid measures

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam. Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

: Flash point = 59 °C. Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Remark

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Flammable liquid and vapor.

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 3/15

## Section 5. Fire-fighting measures

Remark (Explosibility)

: Not considered to be a product presenting a risk of explosion.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version :1 4/15

# Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
pyridate (ISO)	None.
cyclohexanone	ACGIH TLV (United States, 3/2020).  Absorbed through skin.  TWA: 20 ppm 8 hours.  STEL: 50 ppm 15 minutes.  OSHA PEL 1989 (United States, 3/1989).  Absorbed through skin.  TWA: 25 ppm 8 hours.  TWA: 100 mg/m³ 8 hours.  NIOSH REL (United States, 10/2016).  Absorbed through skin.  TWA: 25 ppm 10 hours.  TWA: 25 ppm 10 hours.  TWA: 100 mg/m³ 10 hours.  OSHA PEL (United States, 5/2018).  TWA: 50 ppm 8 hours.  TWA: 200 mg/m³ 8 hours.
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	None.
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	None.
calcium dodecylbenzenesulphonate	None.
2-ethylhexan-1-ol	None.
octane-1-thiol	NIOSH REL (United States, 10/2016). CEIL: 0.5 ppm 15 minutes. CEIL: 3 mg/m³ 15 minutes.

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: When using do not eat, drink or smoke. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Section 8. Exposure controls/personal protection

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. **Recommended:** Ensure an MSHA/NIOSH-approved respirator or equivalent is used.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.

Color : Brownish [Light]
Odor : Not available.
Odor threshold : Not available.

**pH** : 5.6 [Conc. (% w/w): 1%]

Melting point: Not applicable.Boiling point: Not available.Flash point: 59°C (138.2°F)Evaporation rate: Not available.

Flammability (solid, gas) : Flammable liquid and vapor.

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure: Not available.Vapor density: Not available.

Relative density : 1.07

Solubility : Not available.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): 37.1 mPa·s (37.1 cP)

**Explosive properties**: Not considered to be a product presenting a risk of explosion.

Oxidizing properties : None.

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 6/15

# Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not use in the presence of electrostatic discharges.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials

Hazardous decomposition products

: Sulphur dioxide, carbon dioxide, carbon monoxide, hydrogen chloride, nitrogen oxides (NO, NO<sub>2</sub> etc.).

## **Section 11. Toxicological information**

#### **Information on toxicological effects**

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
pyridate (ISO)	LC50 Inhalation Dusts and mists	Rat	>4.37 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
cyclohexanone	LD50 Dermal	Rabbit	950 mg/kg	-
	LD50 Oral	Rat	1750 mg/kg	-
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	LC50 Inhalation Vapor	Rat - Male, Female	>4778 mg/m³	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Tough 5 EC Herbicide	LC50 Inhalation Vapor	Rat	>6.37 mg/l	4 hours
	LD50 Dermal	Rat	>4000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

### Conclusion/Summary Irritation/Corrosion

: Based on available data, the classification criteria are not met.

Product/ingredient name	Result	Species	Score	Exposure	Observation
cyclohexanone	Skin - Moderate irritant	Rabbit	-	-	-
	Eyes - Moderate irritant	Rabbit	-	-	-
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	Skin - Non-irritating to the skin.	Rabbit	-	72 hours	-
	Eyes - Non-irritating to the eyes.	Rabbit	-	72 hours	-
Tough 5 EC Herbicide	Skin - Irritant	Rabbit	-	-	-

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 7/15

# Section 11. Toxicological information

Eyes - Irritant Rabbit - - - -

**Conclusion/Summary** 

Skin : Causes skin irritation.

**Eyes**: Causes serious eye irritation.

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	skin	Guinea pig	Not sensitizing
Tough 5 EC Herbicide	skin	Guinea pig	Sensitizing

#### **Conclusion/Summary**

**Skin** : May cause an allergic skin reaction.

#### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 476	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 475	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

**Classification** 

Product/ingredient name	OSHA	IARC	NTP
cyclohexanone	-	3	-

#### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	Negative	Negative	Negative	Rat - Male, Female		6 hours; 5 days per week

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

#### **Teratogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	Negative - Oral	Rat	5 5	21 days; 7 days per week

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
2-ethylhexan-1-ol	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 8/15

# Section 11. Toxicological information

Name	Result
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate :

effects

: Not available.

Potential delayed effects : Not available.

#### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	Sub-chronic NOAEL Oral	Rat - Male, Female	300 mg/kg	13 weeks; 7 days per week
	Chronic NOAEL Inhalation Vapor	Rat - Female	900 mg/m³	12 months; 5 days per week

**Conclusion/Summary**: Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

## Numerical measures of toxicity

**Acute toxicity estimates** 

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 9/15

# Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
Tough 5 EC Herbicide	2500	2500	N/A	40.7	N/A
pyridate (ISO)	2500	2500	N/A	N/A	N/A
cyclohexanone	1750	1100	N/A	11	N/A
Hydrocarbons, C10-C13, aromatics, <1% naphthalene	N/A	2500	N/A	N/A	N/A
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	N/A	N/A	N/A	11	N/A
calcium dodecylbenzenesulphonate	500	N/A	N/A	N/A	N/A
2-ethylhexan-1-ol	N/A	N/A	N/A	11	N/A

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
pyridate (ISO)	Acute EC50 >0.75 mg/l	Algae	72 hours
	Acute EC50 0.49 mg/l	Daphnia	48 hours
	Acute LC50 >1 mg/l	Fish	96 hours
	Chronic NOEC 0.01 mg/l	Crustaceans	21 days
Tough 5 EC Herbicide	Acute EC50 0.0464 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0.04 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 2.59 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.063 mg/l	Crustaceans - Daphnia Magna	21 days
	Chronic NOEC 0.1 mg/l	Fish - Oncorhynchus mykiss	21 days

**Conclusion/Summary** 

: Very toxic to aquatic life with long lasting effects.

#### Persistence and degradability

**Conclusion/Summary**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	-	-	Not readily

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
pyridate (ISO)	4.01	116.3	low

### **Mobility in soil**

Date of issue/Date of revision: 09/17/2020Date of previous issue: No previous validationVersion: 1

# Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS#	Status	Reference number
Cyclohexanone (I)	108-94-1	Listed	U057

# **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	UN1915	UN1915	UN1915	UN1915	UN1915	UN1915
UN proper shipping name	Cyclohexanone, solution	CYCLOHEXANONE, solution	CICLOHEXANONA, solution	CYCLOHEXANONE, solution	CYCLOHEXANONE, solution	Cyclohexanone, solution
Transport hazard class(es)	3	3	3	3	3	3
Label	TANNAL JOIN					
Packing group	III	III	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Marine Pollutant: Yes	Yes. The environmentally hazardous substance mark is not required.

**Additional information** 

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 11/15

## Section 14. Transport information

#### **DOT Classification**

: This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids, that are marine pollutants, are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by vessel.

This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a. Reportable quantity 22935.8 lbs / 10412.8 kg [2570.8 gal / 9731.6 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

Limited quantity Yes.

Packaging instruction Exceptions: 150. Non-bulk: 203. Bulk: 242. **Quantity limitation** Passenger aircraft/rail: 60 L. Cargo aircraft: 220 L.

Special provisions B1, IB3, T2, TP1

#### **TDG Classification**

: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.

**Explosive Limit and Limited Quantity Index** 5 Passenger Carrying Road or Rail Index 60

ADR/RID

: The environmentally hazardous substance mark is not required when transported in

sizes of ≤5 L or ≤5 kg.

**Hazard identification number** 30

**Limited quantity** 5 L Tunnel code (D/E)

**IMDG** 

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Emergency schedules F-E, S-D

**IATA** : The environmentally hazardous substance mark may appear if required by other

transportation regulations.

Quantity limitation Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger

Aircraft: 10 L. Packaging instructions: Y344.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

# Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Water Act (CWA) 311: calcium dodecylbenzenesulphonate

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602 **Class I Substances** 

: Not listed

**Clean Air Act Section 602** 

: Not listed

**Class II Substances** 

: Not listed

**DEA List I Chemicals** (Precursor Chemicals)

**DEA List II Chemicals** (Essential Chemicals) : Not listed

**SARA 302/304** 

**Composition/information on ingredients** 

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version :1 12/15

# Section 15. Regulatory information

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : FLAMMABLE LIQUIDS - Category 3

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

#### **Composition/information on ingredients**

Name	%	Classification
pyridate (ISO)	≥50 - ≤75	SKIN IRRITATION - Category 2
		SKIN SENSITIZATION - Category 1
cyclohexanone	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 3
		ACUTE TOXICITY (oral) - Category 4
		ACUTE TOXICITY (dermal) - Category 4
		ACUTE TOXICITY (inhalation) - Category 4
		SKIN IRRITATION - Category 2
		SERIOUS EYE DAMAGE - Category 1
Hydrocarbons, C10-C13,	≤10	ASPIRATION HAZARD - Category 1
aromatics, <1% naphthalene		
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	≤5	ACUTE TOXICITY (inhalation) - Category 4
calcium	≤3	ACUTE TOXICITY (oral) - Category 4
dodecylbenzenesulphonate		SKIN IRRITATION - Category 2
acaesylestizeriesalprioriate		SERIOUS EYE DAMAGE - Category 1
2-ethylhexan-1-ol	≤3	ACUTE TOXICITY (inhalation) - Category 4
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		SPECIFIC TARGET ORĞAN TOXICITY (SINGLE EXPOSURE)
		(Respiratory tract irritation) - Category 3
octane-1-thiol	≤0.3	SKIN SENSITIZATION - Category 1

#### **State regulations**

Massachusetts : The following components are listed: CYCLOHEXANONE; CALCIUM

DODECYLBENZENE SULFONATE; 2-ETHYLHEXANOL

New York : The following components are listed: Cyclohexanone; Calcium dodecylbenzene

sulfonate

New Jersey : The following components are listed: CYCLOHEXANONE; CALCIUM

DODECYLBENZENE SULFONATE; BENZENESULFONIC ACID, DODECYL-,

**CALCIUM SALT** 

Pennsylvania: The following components are listed: CYCLOHEXANONE; BENZENESULFONIC ACID,

DODECYL-, CALCIUM SALT; 1-HEXANOL, 2-ETHYL-

#### California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 13/15

# **Section 15. Regulatory information**

Not listed.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.), Fourth Edition



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### **National Fire Protection Association (U.S.A.)**



#### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
SKIN IRRITATION - Category 2	On basis of test data
EYE IRRITATION - Category 2A	On basis of test data
SKIN SENSITIZATION - Category 1	On basis of test data

#### **History**

Date of printing : 09/17/2020 Date of issue/Date of : 09/17/2020

revision

Date of previous issue : No previous validation

Version :

**Key to abbreviations** : ADR = The European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
DOT = Department of Transportation

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

SGG = Segregation Group

TDG = Transportation of Dangerous Goods

UN = United Nations

References : Not available.

▼ Indicates information that has changed from previously issued version.

**Notice to reader** 

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 14/15

# Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 09/17/2020 Date of previous issue : No previous validation Version : 1 15/15